

# Package ‘phenoDist’

April 15, 2017

**Version** 1.22.0

**Title** Phenotypic distance measures

**Author** Xian Zhang, Gregoire Pau, Wolfgang Huber, Michael Boutros

**Maintainer** Xian Zhang <xianzhang@gmail.com>

**Depends** R (>= 2.9.0), imageHTS, e1071

**Suggests** GOstats, MASS

**Description** PhenoDist is designed for measuring phenotypic distance in image-based high-throughput screening, in order to identify strong phenotypes and to group treatments into functional clusters.

**Reference**

**License** LGPL-2.1

**URL** <http://www.dkfz.de/signaling>,  
[http://www.embl.de/research/units/genome\\_biology/huber/](http://www.embl.de/research/units/genome_biology/huber/)

**biocViews** CellBasedAssays

**NeedsCompilation** no

## R topics documented:

clusterDist . . . . .	2
ctlSeparatn . . . . .	3
distToNeg . . . . .	4
enrichAnalysis . . . . .	5
PDMyFactorAnalysis . . . . .	6
PDMyKS . . . . .	7
PDMySvmAccuracy . . . . .	8
PDMySvmWeightVector . . . . .	9
PDMyWellAvg . . . . .	10
repCorr . . . . .	12
repDistRank . . . . .	12

<b>Index</b>	<b>14</b>
--------------	-----------

---

clusterDist	<i>clusterDist</i>
-------------	--------------------

---

### Description

Clustering analysis based on a distance matrix.

### Usage

```
clusterDist(x, distMatrix, clusterFun='hclust', ...)
```

### Arguments

x	An imageHTS object.
distMatrix	A pair-wise distance matrix or a dist object.
clusterFun	A character string defining the cluster function.
...	Additional arguments to be passed to the cluster function.

### Details

This function performs a clustering analysis based on a pair-wise distance matrix such as generated by PDMySvmAccuracy.

### Value

The return from the cluster function, such as an hclust object returned from the hclust function.

### Author(s)

Xian Zhang

### See Also

hclust, PDMySvmAccuracy

### Examples

```
library('phenoDist')

## load the imageHTS object
load(system.file('kimorph', 'kimorph.rda', package='phenoDist'))
x@localPath <- file.path(tempdir(), 'kimorph')

## load sample phenotypic distance matrix
load(system.file('kimorph', 'svmAccPDM_P11.rda', package='phenoDist'))

## phenotypic clustering
phenoCluster <- clusterDist(x, distMatrix=svmAccPDM_P11, clusterFun='hclust', method='ward')

## Not run:
require('GOstats')
GOEnrich <- enrichAnalysis(x, cl=cutree(phenoCluster, k=5), terms='GO', annotation='org.Hs.eg.db', pvalueC
```

```
## End(Not run)
```

---

ctlSeparatn                      *Calculate control separation*

---

### Description

This function calculates the  $Z'$ -factor between negative and positive controls, based on phenotypic distance measurements.

### Usage

```
ctlSeparatn(x, pheno, neg='rluc', pos='ubc', ...)
```

### Arguments

x	An imageHTS object.
pheno	A numeric vector for distances to negative controls, as returned from <code>distToNeg</code> .
neg	A character string to identify negative controls.
pos	A character string to identify positive controls.
...	Additional arguments to be passed to the <code>Zprime</code> function of the <code>imageHTS</code> package.

### Details

Phenotypes of negative and positive controls are defined as their phenotypic distance to negative controls. The  $Z'$ -factor is a metric measuring the separation between negative controls and positive controls (Zhang et al. 1999). This function calls the `Zprime` function of the `imageHTS` package to calculate the  $Z'$ -factor. Please see `Zprime` for detailed description of the definition and calculation of the  $Z'$ -factor.

### Value

The  $Z'$ -factor value.

### Author(s)

Xian Zhang

### References

J. H. Zhang, T. D. Chung, K. R. Oldenburg. A Simple Statistical Parameter for Use in Evaluation and Validation of High Throughput Screening Assays. *J Biomol Screening*, 1999.

### See Also

`distToNeg`, `Zprime`

### Examples

```
## see distToNeg.
```

---

`distToNeg`*distToNeg*

---

**Description**

From a pair-wise distance matrix, this function extracts the corresponding distance between a sample and negative controls.

**Usage**

```
distToNeg(x, distMatrix, neg='rluc')
```

**Arguments**

<code>x</code>	An imageHTS object
<code>distMatrix</code>	A pair-wise distance matrix, as generated by PDMySvmAccuracy.
<code>neg</code>	A character string to identify negative controls.

**Details**

This function averages the distance measurements between the sample and all negative controls on the same plate.

**Value**

A numeric vector with length equal to the dimension of the distance matrix.

**Author(s)**

Xian Zhang

**See Also**

PDMySvmAccuracy

**Examples**

```
library('phenoDist')

## load the imageHTS object
load(system.file('kimorph', 'kimorph.rda', package='phenoDist'))
x@localPath <- file.path(tempdir(), 'kimorph')

## load sample phenotypic distance matrix
load(system.file('kimorph', 'svmAccPDM_P11.rda', package='phenoDist'))

## replicate ranking
ranking <- repDistRank(x, distMatrix=svmAccPDM_P11)
summary(ranking)

## phenotypic distance to negative control
pheno <- distToNeg(x, distMatrix=svmAccPDM_P11, neg='rluc')
```

```
## separation between negative and positive controls
ctlSeparatn(x, pheno, neg='rluc', pos='ubc', method='robust')

## replicate correlation coefficient
repCorr(x, pheno)
```

---

enrichAnalysis	<i>enrichAnalysis</i>
----------------	-----------------------

---

## Description

This function performs enrichment analysis on genes within each cluster, with genes from all clusters as the gene universe.

## Usage

```
enrichAnalysis(x, cl, terms=c('GO', 'KEGG'), verbose=FALSE, ...)
```

## Arguments

x	An imageHTS object.
cl	A named numeric vector, with names being gene Entrez IDs and values indicating grouping.
terms	A character string indicating which annotation should be used. This must be (an abbreviation of) one of the strings 'GO' or 'KEGG'.
verbose	A logical scalar indicating whether progress should be reported.
...	Additional arguments to be passed to the hyperGTest function of the G0stats package.

## Details

Gene enrichment analysis tests whether certain gene annotations (e.g., GO terms or KEGG ids) are enriched in genes of interest, compared with the gene universe. This function is designed to analyze gene enrichment in clusters, with genes in the tested cluster being genes of interest and genes in all clusters being the gene universe.

The Hypergeometric test is performed by the hyperGTest function of the G0stats package. Please refer to hyperGTest for additional arguments.

## Value

A list of HyperGResult instances.

## Author(s)

Xian Zhang

## See Also

G0stats, clusterDist

**Examples**

```
## see clusterDist.
```

---

PDMyFactorAnalysis     *Calculate phenotypic distance matrix by factor analysis*

---

**Description**

This function transforms the cell features by factor analysis and computes the phenotypic distance matrix.

**Usage**

```
PDMyFactorAnalysis(x, unames, selectedCellFtrs, distMethod=c('manhattan', 'euclidean', 'correlation', 'mahalanobis'))
```

**Arguments**

x	An imageHTS object.
unames	A character vector, containing the well names from where to collect the cell features. See getUnames for details.
selectedCellFtrs	A character vector for cell features to be used in the calculation. If missing, all features are used.
distMethod	A character string indicating which distance method should be used. This must be (an abbreviation of) one of the strings 'manhattan', 'euclidean', 'correlation' or 'mahalanobis'.
nFactors	An integer scalar for the number of factors.
scores	A character string indicating the type of scores to be reported by factor analysis. This must be (an abbreviation of) one of the strings 'regression' or 'Bartlett'.
...	Additional arguments to be passed to the factanal function of the stats package.

**Details**

This function first collects individual cell features in all wells (which could be time and memory consuming), performs factor analysis on cell features and transforms cell features into a certain number of factors, and then the factors are averaged by well and passed to PDMyWellAvg to calculate the phenotypic distance matrix.

**Value**

A symmetric distance matrix with dimensions equaling to the length of unames.

**Author(s)**

Xian Zhang

**See Also**

factanal, PDMyWellAvg

**Examples**

```
library('phenoDist')

## load the imageHTS object
load(system.file('kimorph', 'kimorph.rda', package='phenoDist'))
x@localPath <- file.path(tempdir(), 'kimorph')

## segmentation and feature extraction
unames <- setdiff(getUnames(x), getUnames(x, content='empty'))

## calculate pair-wise svm distance matrix
load(system.file('kimorph', 'selectedFtrs.rda', package='phenoDist'))
pdm <- PDMyFactorAnalysis(x, unames=getUnames(x, plate=1, row=2:3, col=3), selectedCellFtrs, distMethod='pdm')
```

---

PDMyKS

*Compute phenotypic distance matrix by Kolmogorov-Smirnov statistics*

---

**Description**

This function calculates the Kolmogorov-Smirnov statistic between a given sample and the negative control, for each feature, and then computes the phenotypic distance matrix based on the Kolmogorov-Smirnov statistics.

**Usage**

```
PDMyKS(x, unames, neg='rluc', selectedCellFtrs, distMethod=c('manhattan', 'euclidean', 'correlation'))
```

**Arguments**

x	An imageHTS object.
unames	A character vector, containing the well names from where to collect the cell features. See getUnames for details.
neg	A character string to identify negative controls.
selectedCellFtrs	A character vector for cell features to be used in the calculation. If missing, all features are used.
distMethod	A character string indicating which distance method should be used. This must be (an abbreviation of) one of the strings 'manhattan', 'euclidean', 'correlation' or 'mahalanobis'.

**Details**

For each well, this function collects features of all cells, and performs a Kolmogorov-Smirnov test for each feature against the corresponding cell features from negative control wells, with the function `ks.test` of the `stats` package. The Kolmogorov-Smirnov statistics are collected for all wells and passed to `PDMyWellAvg` to calculate the phenotypic distance matrix.

**Value**

A symmetric distance matrix with the number of rows equaling to the length of unames.

**Author(s)**

Xian Zhang

**See Also**

ks.test, PDmByWellAvg

**Examples**

```
library('phenoDist')

## load the imageHTS object
load(system.file('kimorph', 'kimorph.rda', package='phenoDist'))
x@localPath <- file.path(tempdir(), 'kimorph')

## calculate pair-wise svm distance matrix
load(system.file('kimorph', 'selectedFtrs.rda', package='phenoDist'))
pdm <- PDmByKS(x, unames=getUnames(x,plate=1, row=2:3, col=3), neg='rluc', selectedCellFtrs=selectedCellFtrs)
pdm
```

---

PDmBySvmAccuracy

*Compute phenotypic distance matrix by SVM classification accuracy*

---

**Description**

This function performs an SVM classification between two given samples, and calculates the classification accuracy via cross validation as the phenotypic distance between the two samples. For multiple samples, the function returns a pair-wise distance matrix.

**Usage**

```
PDmBySvmAccuracy(x, unames, selectedCellFtrs, cross=5, verbose=FALSE, ...)
```

**Arguments**

x	An imageHTS object.
unames	A character vector, containing the well names from where to collect the cell features. See getUnames for details.
selectedCellFtrs	A character vector for cell features to be used in the calculation. If missing, all features are used.
cross	An interger scalar indicating how many folds of cross validation should be performed.
verbose	A logical scalar indicating whether progress should be reported.
...	Additional arguments to be passed to the svm function of the e1071 package.



**Details**

For every pair of wells, this function collects features of all cells from both wells, and performs a bi-class classification using Support Vector Machine (SVM). The classification accuracy is defined as the phenotypic distance for the distance matrix.

**Value**

A symmetric distance matrix with the number of rows equaling to the length of unames.

**Author(s)**

Xian Zhang

**See Also**

svm

**Examples**

```
library('phenoDist')

## load the imageHTS object
load(system.file('kimorph', 'kimorph.rda', package='phenoDist'))
x@localPath <- file.path(tempdir(), 'kimorph')

## calculate pair-wise svm distance matrix
load(system.file('kimorph', 'selectedFtrs.rda', package='phenoDist'))
pdm <- PDmBySvmAccuracy(x, unames=getUnames(x, plate=1, row=2:3, col=3), selectedCellFtrs=selectedCellFtrs)
```

---

PDmBySvmWeightVector    *Compute phenotypic distance matrix by SVM weight vector*

---

**Description**

This function performs an SVM classification between a given sample and the negative control, calculates the weight vector, and then computes the phenotypic distance matrix based on the weight vectors.

**Usage**

```
PDmBySvmWeightVector(x, unames, neg='rluc', selectedCellFtrs, distMethod=c('manhattan','euclidean'))
```

**Arguments**

x	An imageHTS object.
unames	A character vector, containing the well names from where to collect the cell features. See getUnames for details.
neg	A character string to identify the negative controls.

selectedCellFtrs	A character vector for cell features to be used in the calculation. If missing, all features are used.
distMethod	A character string indicating which distance method should be used. This must be (an abbreviation of) one of the strings 'manhattan', 'euclidean', 'correlation' or 'mahalanobis'.
verbose	A logical scalar indicating whether progress should be reported.
kernel	The kernel argument for the svm function of the e1071 package.
...	Additional arguments to be passed to the svm function of the e1071 package.

### Details

For each well, this function collects features of all cells from the well and all cells from the negative control wells, and performs a bi-class classification using Support Vector Machine (SVM). The classification weight vectors are calculated for all wells passed to PDMyWellAvg to compute the phenotypic distance matrix.

### Value

A symmetric distance matrix with dimensions equaling to the length of unames.

### Author(s)

Xian Zhang

### See Also

svm, PDMyWellAvg

### Examples

```
library('phenoDist')

## load the imageHTS object
load(system.file('kimorph', 'kimorph.rda', package='phenoDist'))
x@localPath <- file.path(tempdir(), 'kimorph')

## calculate pair-wise svm distance matrix
load(system.file('kimorph', 'selectedFtrs.rda', package='phenoDist'))
pdm <- PDMySvmWeightVector(x, unames=getUnames(x,plate=1, row=2:3, col=3), neg='rluc', selectedCellFtrs=)
```

---

PDMyWellAvg

*Compute phenotypic distance matrix with well features*

---

### Description

This function computes the phenotypic distance matrix, with cell features averaged by well.

### Usage

```
PDMyWellAvg(profiles, selectedWellFtrs, transformMethod=c('none', 'scale', 'PCA'), distMethod=)
```

## Arguments

<code>profiles</code>	A data frame, containing the phenotypic profiles, as returned from the <code>summarizeWells</code> function of the <code>imageHTS</code> package.
<code>selectedWellFtrs</code>	A character vector indicating well features to be used in the calculation. If missing, all features are used.
<code>transformMethod</code>	A character string indicating which transformation method should be used. This must be (an abbreviation of) one of the strings <code>'none'</code> , <code>'scale'</code> or <code>'PCA'</code> .
<code>distMethod</code>	A character string indicating which distance method should be used. This must be (an abbreviation of) one of the strings <code>'manhattan'</code> , <code>'euclidean'</code> , <code>'correlation'</code> or <code>'mahalanobis'</code> .
<code>nPCA</code>	An integer scalar for the number of PCA dimensions to be used in the calculation.

## Details

Pair-wise phenotypic distance measurements of the treatments in screen results in a phenotypic distance matrix. The features stored in `profiles` are transformed with the `transformMethod` and the distance matrix is calculated with the `distMethod`.

## Value

A symmetric distance matrix with dimensions equaling to the number of rows of `profiles`.

## Author(s)

Xian Zhang

## See Also

`summarizeWells`

## Examples

```
library('phenoDist')

## load the imageHTS object
load(system.file('kimorph', 'kimorph.rda', package='phenoDist'))
x@localPath <- file.path(tempdir(), 'kimorph')

## calculate pair-wise svm distance matrix
load(system.file('kimorph', 'selectedFtrs.rda', package='phenoDist'))
pdm <- PDMPByWellAvg(profiles=summarizeWells(x, getUnames(x,plate=1, row=2:3, col=3), 'conf/featurepar.txt'),
  pdm
```

---

repCorr	<i>repCorr</i>
---------	----------------

---

**Description**

This function calculates the correlation between replicate phenotypes.

**Usage**

```
repCorr(x, pheno, ...)
```

**Arguments**

x	An imageHTS object.
pheno	A numeric vector for distance measures to negative control, as returned from <code>distToNeg</code> .
...	Additional arguments to be passed to the <code>cor</code> function of the <code>stats</code> package.

**Value**

Correlation coefficient returned from the `cor` function of the `stats` package.

**Author(s)**

Xian Zhang

**See Also**

`cor`, `distToNeg`

**Examples**

```
## see distToNeg.
```

---

repDistRank	<i>repDistRank</i>
-------------	--------------------

---

**Description**

For each treatment, this function calculates the ranking of its replicate in terms of phenotypic distance.

**Usage**

```
repDistRank(x, distMatrix)
```

**Arguments**

`x` An imageHTS object.  
`distMatrix` A pair-wise distance matrix or dist object.

**Details**

For each treatment, this function ranks the distance measure to its replicate among the distance measurements to all other treatments.

**Value**

A numeric vector with length equal to the dimension of the distance matrix.

**Author(s)**

Xian Zhang

**See Also**

`PDByWellAvg`

**Examples**

```
## see distToNeg.
```

# Index

clusterDist, [2](#)  
ctlSeparatn, [3](#)

distToNeg, [4](#)

enrichAnalysis, [5](#)

PDmByFactorAnalysis, [6](#)

PDmByKS, [7](#)

PDmBySvmAccuracy, [8](#)

PDmBySvmWeightVector, [9](#)

PDmByWellAvg, [10](#)

repCorr, [12](#)

repDistRank, [12](#)