

htSeqTools: quality control, visualization and processing high-throughput sequencing data

Evarist Planet ^{*}, Camille Stephan-Otto ^{*}, Oscar Reina ^{*},
Oscar Flores [†], David Rossell ^{*}

1 Introduction

The `htSeqTools` package provides an easy-to-use toolset to efficiently perform a variety of tasks with high-throughput sequencing data. Although relatively simple-minded, we found the tools to be extremely helpful in quality control assessment, routine pre-processing and analysis steps and in producing useful visualizations. When using the package please cite Planet et al. [2012]. The supplementary material of the paper should be a useful resource, as it contains a detailed description of the methods and additional examples (including ChIP-Seq, MNase-Seq and RNA-Seq) with R code.

Emphasis is placed on ChIP-Seq alike experiments, but many functions are also useful for other kinds of sequencing experiments.

Many routines allow performing computations in parallel by specifying an argument `mc.cores`, which uses package `parallel`. As this package is not available in all platforms, in this manual we do not use parallel computing. Please see the help page for each function for more details.

We start by loading the package and a ChIP-Seq dataset which we will use for illustration purposes.

```
> options(width=70)
> library(htSeqTools)
> data(htSample)
> htSample
```

```
GRangesList object of length 4:
$ctrlBatch1
```

^{*}Bioinformatics & Biostatistics Unit, IRB Barcelona

[†]IRB-BSC Joint Research Program on Computational Biology, IRB Barcelona

GRanges object with 102866 ranges and 0 metadata columns:

```
      seqnames      ranges strand
      <Rle>       <IRanges> <Rle>
 [1]   chr2L 499167-499206      +
 [2]   chr2L 377930-377969      -
 [3]   chr2L 306297-306336      -
 [4]   chr2L 174413-174452      +
 [5]   chr2L 322795-322834      +
 ...
 [102862] chr2L 318650-318689     +
 [102863] chr2L 294283-294322     -
 [102864] chr2L 420010-420049     +
 [102865] chr2L 292888-292927     -
 [102866] chr2L 252943-252982     -
 ...
<3 more elements>
-----
seqinfo: 1 sequence from an unspecified genome; no seqlengths
> sapply(htSample,length)

ctrlBatch1  ipBatch1 ctrlBatch2  ipBatch2
    102866    195304     59809     99320
```

`htSample` is a `GRangesList` object storing the chromosome, start and end positions for reads mapped to the first 500kb of the *drosophila melanogaster* chromosome 2L. `htSample` contains 2 immuno-precipitated and 2 control input samples obtained in two separate Illumina sequencing runs, which we named Batch1 and Batch2. The standard Illumina pipeline was used for pre-processing the data. Following the Bowtie defaults, only uniquely mapping reads with at most 2 mismatches in the first 28 bases were kept. We do not give any further details about the experiment, as the results have not yet been published.

You can easily build a `GRangesList` to store multiple `GRanges` objects (coming from different BED files read as data frames for instance). We will extract two elements from `htSample` in order to simulate a batch of 2 externally loaded samples. `Ctrl` and `IP1` will be two data frames with 'seqnames', 'start', 'end', 'width', and 'strand' columns. Please note that only 'seqnames', 'start' and 'end' are necessary in order to directly generate a `GRanges` object from a data frame. The 'width' and 'strand' column are optional and any additional column will be added to the `GRanges` object as a metadata column.

```
> Ctrl=as.data.frame(htSample[[1]])
> IP1=as.data.frame(htSample[[2]])
> head(Ctrl)
```

	seqnames	start	end	width	strand
1	chr2L	499167	499206	40	+
2	chr2L	377930	377969	40	-
3	chr2L	306297	306336	40	-
4	chr2L	174413	174452	40	+
5	chr2L	322795	322834	40	+
6	chr2L	415508	415547	40	+

```
> makeGRangesFromDataFrame(Ctrl)
```

GRanges object with 102866 ranges and 0 metadata columns:

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	chr2L	499167-499206	+
[2]	chr2L	377930-377969	-
[3]	chr2L	306297-306336	-
[4]	chr2L	174413-174452	+
[5]	chr2L	322795-322834	+
...
[102862]	chr2L	318650-318689	+
[102863]	chr2L	294283-294322	-
[102864]	chr2L	420010-420049	+
[102865]	chr2L	292888-292927	-
[102866]	chr2L	252943-252982	-

seqinfo: 1 sequence from an unspecified genome; no seqlengths

```
> htSample2 <- GRangesList(Ctrl=makeGRangesFromDataFrame(Ctrl),
+                           IP1=makeGRangesFromDataFrame(IP1))
> htSample2
```

GRangesList object of length 2:

\$Ctrl

GRanges object with 102866 ranges and 0 metadata columns:

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	chr2L	499167-499206	+
[2]	chr2L	377930-377969	-
[3]	chr2L	306297-306336	-
[4]	chr2L	174413-174452	+
[5]	chr2L	322795-322834	+
...
[102862]	chr2L	318650-318689	+
[102863]	chr2L	294283-294322	-
[102864]	chr2L	420010-420049	+
[102865]	chr2L	292888-292927	-
[102866]	chr2L	252943-252982	-

...
<1 more element>

```

-----
seqinfo: 1 sequence from an unspecified genome; no seqlengths

> htSample2[['Ctrl']]

GRanges object with 102866 ranges and 0 metadata columns:
      seqnames      ranges strand
   <Rle>      <IRanges> <Rle>
 [1]  chr2L  499167-499206      +
 [2]  chr2L  377930-377969      -
 [3]  chr2L  306297-306336      -
 [4]  chr2L  174413-174452      +
 [5]  chr2L  322795-322834      +
 ...      ...      ...      ...
[102862] chr2L  318650-318689      +
[102863] chr2L  294283-294322      -
[102864] chr2L  420010-420049      +
[102865] chr2L  292888-292927      -
[102866] chr2L  252943-252982      -
-----
seqinfo: 1 sequence from an unspecified genome; no seqlengths

```

2 Quality control

2.1 A PCA analogue for sequencing data

PCA is a commonly used technique to assess overall quality and identify problematic samples in high-throughput experiments. PCA requires to define a common set of entities (e.g. genes) for all samples and obtain some numerical measurement for each entity in each sample (e.g. gene expression). Therefore, unfortunately PCA is not directly applicable to sequencing data. One option is to pre-process the data so that PCA can be applied, e.g. computing the number of reads falling in some pre-defined genomic regions. The inconvenient of this approach is its lack of generality, since different kinds of sequencing data generally require different pre-processing. For instance, while in RNA-Seq we can obtain a PCA based on RPKM expression measures [Mortazavi et al., 2008], this same strategy is not adequate for ChIP-Seq data where many reads may be mapped to promoter or inter-genic regions.

Instead, we propose comparing the read coverage across samples and using Multi-Dimensional Scaling (MDS) to obtain a low-dimensional visual representation. Read coverage is a universal measure which can be computed efficiently for any type of sequencing data. We measure similarity between samples i and j with ρ_{ij} , the correlation between their log-coverages, and define their distance as $d_{ij} = 0.5(1 - \rho_{ij})$. Pearson, Spearman and Kendall

correlation coefficients are available. We compute correlations in the log-scale to take into account that the coverage distribution is typically highly asymmetric. In principle, Spearman is more general as it captures non-linear associations, but in practice all options typically produce very similar results. MDS is then used to plot the samples in a low-dimensional space, in a way such that the Euclidean distance between two points is closest to the Pearson distances. Our approach is implemented in a `cmds` method for `GRangesList` objects. We illustrate its use by obtaining a two-dimensional MDS for our sample data.

```
> cmds1 <- cmds(htSample,k=2)

Computing coverage...
Computing correlations...

> cmds1

Object of class cmdsFit approximating distances between 4 objects
R-squared= 1
```

The R^2 coefficient between the original distances and their approximation in the plot can be seen as an analogue to the percentage of explained variability in a PCA analysis. For our sample data $R^2=1$ (up to rounding), which indicates a perfect fit and that therefore a 3-dimensional plot is not necessary.

```
> plot(cmds1)
```

Figure 1 shows the resulting plot. The IP samples from both runs group nicely, indicating that they have similar coverage profiles. The control samples also group reasonably well, although they present more differences than the IP samples. This is to be expected, since the IP samples focus on a relatively small genomic regions. The MDS plot also reveals a minor batch effect, as samples from the same batch appear slightly closer in the map.

2.2 Exploring coverage uniformity

In some next-generation sequencing experiments we expect some samples to exhibit large accumulations of reads in certain genomic regions, whereas other samples should present a more uniform coverage along the genome. For instance, in ChIP-seq one should observe higher peaks for immuno-precipitated (IP) samples than in the controls. That is, IP samples should present coverage rich and coverage poor regions, whereas differences in coverage in the controls should be smaller.




Figure 1: 2-dimensional MDS plot. Samples with similar coverage appear close-by

In these cases we propose to measure the unevenness in the coverage using either the coverage standard deviation or Gini's coefficient [Gini, 1912], which is a classical econometrics measure to assess unevenness of wealth distribution. Comparing these statistical dispersion measures between samples can reveal samples with inefficient immuno-precipitation (e.g. due to an inadequate antibody). Both measures can be easily obtained with the functions `ssdCoverage` and `giniCoverage`. Simple algebra shows that the expected value of the coverage standard deviation is proportional to \sqrt{n} , where n is the number of reads. Therefore `ssdCoverage` reports $SD_n = SD/\sqrt{n}$ as a measure that can be compared across samples with different number of reads. Similarly, simulations show that the expected Gini also depends on n . Since no closed-form expression is available, we estimate its expected value by generating n reads uniformly distributed along the genome and computing the Gini coefficient. The adjusted Gini (G_n) is the difference between the observed Gini (G) minus its estimated expected value $\hat{E}(G|n)$.

```
> ssdCoverage(htSample)

ctrlBatch1  ipBatch1 ctrlBatch2  ipBatch2
  55.98648  169.15785   18.14517  100.43349

> giniCoverage(htSample,mc.cores=1)

Simulating uniformly distributed data
Calculating gini index of original data
Simulating uniformly distributed data
Calculating gini index of original data
Simulating uniformly distributed data
Calculating gini index of original data
Simulating uniformly distributed data
Calculating gini index of original data
          gini gini.adjust
ctrlBatch1 0.8038884  0.6081955
ipBatch1   0.9378820  0.7975172
ctrlBatch2 0.4813761  0.2269625
ipBatch2   0.9127399  0.7127598
```

The coverage exhibits higher dispersion in the IP samples than in the controls, which indicates there were no substantial problems in the immuno-precipitation. The function `giniCoverage` allows to graphically assess the non-uniformity in the coverage distribution by plotting the probability and cumulative probability function. The top panels in Figure 2 show the log probability mass function of the coverage, and the bottom panels show the Lorenz curve (Gastwirth [1972], see `Lc` from package `ineq` for details). We observe a more pronounced non-uniformity in the IP sample.

```
> giniCoverage(htSample[['ctrlBatch2']],mc.cores=1,mk.plot=TRUE)
```




Figure 2: Lorenz curves to assess coverage uniformity. Left: control; Right: immuno-precipitated sample

```
> giniCoverage(htSample[['ipBatch2']],mc.cores=1,mk.plot=TRUE)
```

2.3 Detecting over-amplification artifacts

High-throughput sequencing requires a PCR amplification step to enrich for adapter-ligated fragments. This step can induce biases as some DNA regions amplify more efficiently than others (e.g. depending on GC content). These PCR artifacts, caused by over-amplification or primer dimers, affect the accuracy of the coverage and can create biases in the downstream analyses. The function `filterDupReads` aims to automatically detect and remove these artifacts. The basic rationale is that, by counting the number of times that each read is repeated, we can detect the reads repeating an unusually large number of times. The argument `maxRepeats` can be used to eliminate all reads appearing more than this user-specified threshold. However, notice that ideally this threshold should be determined for each sample separately, as the expected number of naturally occurring repeats depends on the sequencing depth, and may also depend on the characteristics of each sample. For instance, sequences from IP samples focus on a relatively small genomic region while those from controls are distributed along most of the genome, and therefore we expect a higher number of repeats in IP samples. When specifying the argument `fdrOverAmp`, `filterDupReads` determines the threshold in a data-adaptive manner.

Although this filtering can be performed with a single call to `filterDuplReads`, we now illustrate its inner workings in a step-by-step fashion. We add 200 repeats of an artificial sequence to sample "ctrlBatch1", and count the number of times that each sequence appears with the function `tabDuplReads`.

```
> contamSample <- GRanges('chr2L', IRanges(rep(1,200),rep(36,200)),strand='+')
> contamSample <- c(htSample[['ctrlBatch1']],contamSample)
> nrepeats <- tabDuplReads(contamSample)
> nrepeats
```

ans										
1	2	3	4	5	6	7	8	9	10	11
11812	10112	6744	4083	2325	1343	727	447	212	113	87
12	13	14	15	16	17	18	19	20	22	200
57	35	19	9	9	4	5	1	2	1	1

There are 11812 sequences appearing only once, 10112 appearing twice etc. The function `fdrEnrichedCounts` (called by `filterDuplReads`) determines the over-amplification threshold in a data-adaptive manner. Basically, it assumes that only large number of repeats are artifacts and models the reads with few repeats with a truncated negative binomial mixture (fit via Maximum Likelihood), which we observed to fit experimental data reasonably well. The number of components to be used is chosen in parameter `components`. If this parameter has value 0 the optimal number of components is selected using the Bayesian information criterion (BIC). Here we used one component for computational speed. An empirical Bayes approach similar to that in Efron et al. [2001] is then used to estimate the FDR associated with a given cutoff (see `help(fdrEnrichedCounts)` for details).

```
> q <- which(cumsum(nrepeats/sum(nrepeats))>.999)[1]
> q
```

14
14

```
> fdrest <- fdrEnrichedCounts(nrepeats, use=1:q, components=1)
> numRepeArtif <- rownames(fdrest[fdrest$fdrEnriched<0.01,])[1]
> numRepeArtif
```

[1] "25"

Here we assumed that less than 1/1000 reads are artifacts and fit a negative binomial truncated at [1, 14]. Notice that, although here we used `fdrEnrichedCounts` to detect over-amplification, it can also be used in any other setup when one wishes to detect large counts. In Figure 3 we produce a plot showing the estimated FDR for a series of cutoffs. The argument




Figure 3: Black line: estimated FDR for each number of repeats cutoff. Red line: distribution of the number of repeats as estimated by a truncated negative binomial with 2 components (representing not over-amplified reads). Blue line: distribution of the number of repeats in the observed data.

`fdrOverAmp` to `filterDuplReads` indicates the FDR cutoff to determine over-amplification. We also show the distribution of the observed number of repeats (blue) and its truncated negative binomial approximation in [1, 14] (red). Notice that any sequence repeating over 25 times (including our artificial sequence repeating 200 times) is regarded as an artifact.

```
> plot(fdrest$fdrEnriched,type='l',ylab='',xlab='Number of repeats (r)')
> lines(fdrest$pdfOverall,col=4)
> lines(fdrest$pdfH0,col=2,lty=2)
> legend('topright',c('FDR','P(r | no artifact)','P(r)'),lty=c(1,2,1),col=c(1,2,4))
```

3 Data pre-processing

We discuss several tools which can be useful for ChIP-seq data preprocessing. In these studies there typically is a strand-specific bias: reads coming from the + strand pile up to the left of reads from the - strand. Removing this bias is important, as it provides a highly increased accuracy for peak detection. `alignPeaks` implements a procedure to correct this bias, which is fairly similar to the MACS procedure [Zhang et al., 2008]. A nice alternative is provided in function `estimate.mean.fraglen` from package `chipseq`.

To illustrate the need for the adjustment we plot the coverage in a certain genomic region before the adjustment (displayed in Figure 4, left panel).

```
> covbefore <- coverage(htSample[['ipBatch2']])
> covbefore <- window(covbefore[['chr2L']],295108,297413)
> plot(as.integer(covbefore),type='l',ylab='Coverage')
```

Now we perform the adjustment with `alignPeaks` and plot the resulting coverage as the solid black line in Figure 4 (right panel). In blue and red color we display the coverage computed separately from reads on the + and - strands, respectively. The blue and red lines present a similar profile, but they are shifted. Exploring other peaks reveals similar patterns. Removing this strand specific bias results in sharper peaks and prevents detecting two separate peaks when there should actually be one, as illustrated by the left-most peak in Figure 4.

```
> ip2Aligned <- alignPeaks(htSample[['ipBatch2']],strand='strand', npeaks=100)
Estimated shift size is 61.49423
> covafter <- coverage(ip2Aligned)
> covafter <- window(covafter[['chr2L']],295108,297413)
> covplus <- coverage(htSample[['ipBatch2']][strand(htSample[['ipBatch2']])=='+'])
> covplus <- window(covplus[['chr2L']],295108,297413)
> covminus <- coverage(htSample[['ipBatch2']][strand(htSample[['ipBatch2']])=='-'])
> covminus <- window(covminus[['chr2L']],295108,297413)
> plot(as.integer(covafter),type='l',ylab='Coverage')
> lines(as.integer(covplus),col='blue',lty=2)
> lines(as.integer(covminus),col='red',lty=2)
```

In ChIP-seq experiments, it is sometimes convenient to extend the reads to take into account that we only sequenced the first few bases (typically 40-100 bp) from a larger DNA fragment (typically around 300bp). In practice, this achieves some smoothing of the read coverage. `extendRanges` extends the reads up to a user-specified length.

4 Basic data analysis

Finding genomic regions with large accumulation of reads is an important task in many sequencing experiments, including ChIP-Seq and RNA-Seq. `islandCounts` performs a simple analysis using tools provided in the `IRanges` package. We search for genomic regions with an overall coverage ≥ 10 (i.e. across all samples), and obtain the number of reads in each sample overlapping with these regions.




Figure 4: Coverage for gene p38b. Left: Before adjustment; Right: After adjustment. Blue line: + strand; Red line: - strand; Black line: global estimate after peak alignment by `alignPeaks`.

```
> ip <- c(htSample[[2]],htSample[[4]])
> ctrl <- c(htSample[[1]],htSample[[3]])
> pool <- GRangesList(ip=ip, ctrl=ctrl)
> counts <- islandCounts(pool,minReads=10)
> head(counts)
```

```
GRanges object with 6 ranges and 2 metadata columns:
      seqnames  ranges strand |      ip      ctrl
      <Rle> <IRanges> <Rle> | <integer> <integer>
[1]  chr2L 5191-5211   * |      7      5
[2]  chr2L 5214-5227   * |      9      4
[3]  chr2L 5411-5476   * |     15     14
[4]  chr2L      5484   * |      5      5
[5]  chr2L 5602-5645   * |     13     13
[6]  chr2L 5650-5652   * |      7      3
```

```
-----
seqinfo: 1 sequence from an unspecified genome; no seqlengths
```

There are a number of analysis strategies to compare these counts between groups. For instance for short RNA sequencing data we could compare expression levels across groups using the tools in package `DEseq`. Here we show a simple analysis based on likelihood-ratio tests with the function `enrichedRegions`.

```
> mappedreads <- c(ip=length(ip),ctrl=length(ctrl))
> mappedreads
```

```
ip ctrl
294624 162675
```

```
> regions <- enrichedRegions(sample1=ip,sample2=ctrl,minReads=10,mappedreads=mappedreads,p.adjust)
> head(regions)
```

GRanges object with 6 ranges and 5 metadata columns:

	seqnames	ranges	strand	sample1	sample2
	<Rle>	<IRanges>	<Rle>	<integer>	<integer>
[1]	chr2L	66674-67923	*	651	249
[2]	chr2L	72428-73199	*	2044	200
[3]	chr2L	73357-74080	*	991	144
[4]	chr2L	74484	*	10	0
[5]	chr2L	86284-86285	*	10	0
[6]	chr2L	86294-87202	*	898	260

	pvalue	rpkm1	rpkm2
	<numeric>	<numeric>	<numeric>
[1]	8.07214328893402e-05	1767.67676767677	1224.52743199631
[2]	0	8986.60120622347	1592.54561249702
[3]	0	4645.8690751152	1222.65269785959
[4]	0.0431594471248686	33941.5661996307	0
[5]	0.0431594471248686	16970.7830998154	0
[6]	0	3353.08321752127	1758.28248262048

seqinfo: 1 sequence from an unspecified genome; no seqlengths

```
> nrow(regions)
```

```
NULL
```

The argument `twoTailed=FALSE` indicates that only regions with a significantly higher number of reads in `sample1` than in `sample2` are reported. Regions with overall coverage ≥ 10 are selected, and a likelihood-ratio test is used to compare the proportion of reads in `sample1` falling in a given region with the proportion in `sample2`. When setting `exact` to `TRUE`, a permutation-based Chi-square test is used whenever the expected counts in any group is below 5. Here we reported only regions with Benjamini-Yekutielli adjusted p-values below 0.05.

`enrichedRegions` can also be used with no control sample, in which case it looks for islands with a significant accumulation of reads with an exact Binomial test. The null hypothesis assumes that a read is equally likely to come from any of the selected regions.

A related function is `enrichedPeaks`, which can be used to find peaks within the enriched regions. Peaks are defined as enriched regions where the difference in coverage between `sample1` and `sample2` is above a user-specified threshold. In this example we use `minHeight=100`.

```
> peaks <- enrichedPeaks(regions, sample1=ip, sample2=ctrl, minHeight=100)
> peaks
```

GRanges object with 162 ranges and 2 metadata columns:

	seqnames	ranges	strand	height	region.pvalue
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	chr2L	72615-72665	*	141	0
[2]	chr2L	72668-72940	*	233	0
[3]	chr2L	72988-72994	*	114	0
[4]	chr2L	72996-72997	*	100	0
[5]	chr2L	73475	*	100	0
...
[158]	chr2L	491339-491341	*	102	0
[159]	chr2L	491345-491347	*	104	0
[160]	chr2L	491349	*	102	0
[161]	chr2L	491354-491379	*	113	0
[162]	chr2L	491382-491384	*	103	0

```
-----
seqinfo: 1 sequence from an unspecified genome; no seqlengths
```

It is possible to merge nearby regions, e.g. say no more than 300bp apart, into a single region with the function `mergeRegions`. `mergeRegions` allows to combine a numerical score across regions with any user-defined function, e.g. the mean or median. In the following example we merge regions less than 300bp apart and compute their median 'height'.

```
> mergeRegions(peaks, maxDist=300, score='height', aggregateFUN='median')
```

GRanges object with 35 ranges and 1 metadata column:

	seqnames	ranges	strand	height
	<Rle>	<IRanges>	<Rle>	<numeric>
[1]	chr2L	72615-72997	*	127.5
[2]	chr2L	73475-73712	*	102
[3]	chr2L	102368-103198	*	935.5
[4]	chr2L	106082-106784	*	1272
[5]	chr2L	108119-109322	*	108
...
[31]	chr2L	431278-432063	*	116.5
[32]	chr2L	453202-453882	*	531
[33]	chr2L	473207-473721	*	508
[34]	chr2L	478840-479586	*	342.5
[35]	chr2L	491110-491384	*	103.5

```
-----
seqinfo: 1 sequence from an unspecified genome; no seqlengths
```

A common task is to identify genomic features close to the identified regions/peaks, e.g. finding the closest gene. This can be performed with the function `annotatePeakInBatch` from package `ChIPpeakAnno`, for instance. Sometimes it is of interest to compare the list of genes which had a nearby

peak with the genes found in another experiment. The function `listOverlap` quantifies the overlap and tests for its statistical significance.

Another analysis which may be of interest is locating hot chromosomal regions, i.e., regions in the chromosome with a large number of peaks. The function `enrichedChrRegions` can be used for this purpose. First we need to define a named vector indicating the chromosome lengths. Since our example data only contains reads aligning to the first 500,000 bases of chr2L, we manually its length. More generally, one can determine the chromosome lengths from Bioconductor packages (e.g. for drosophila melanogaster load `BSgenome.Dmelanogaster.UCSC.dm3` and evaluate `seqlengths(Dmelanogaster)`, and similarly for other organisms). We run the function setting a window size of 9999 base pairs and a 0.05 false discovery rate level. For computational speed here we only use `nSims=1` simulations to estimate the FDR.

```
> chrLength <- 500000
> names(chrLength) <- c('chr2L')
> chrregions <- enrichedChrRegions(peaks, chrLength=chrLength, windowSize=10^4-1, fdr=0.05, nSims=1)
> chrregions
```

GRanges object with 11 ranges and 0 metadata columns:

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	chr2L	68708-77639	*
[2]	chr2L	104266-113558	*
[3]	chr2L	150732-161683	*
[4]	chr2L	203117-212706	*
[5]	chr2L	244550-255472	*
[6]	chr2L	272320-276407	*
[7]	chr2L	277654-282740	*
[8]	chr2L	292857-301000	*
[9]	chr2L	301160-302862	*
[10]	chr2L	413952-419140	*
[11]	chr2L	486367-491383	*

seqinfo: 1 sequence from an unspecified genome; no seqlengths

`enrichedChrRegions` returns a `GRanges` which for our sample data is empty, suggesting that there is no region with an unusually high density of enriched regions. Two related functions are `countHitsWindow` which computes the moving average of the number of hits, and `plotChrRegions` to visualize the results. For illustrative purposes we make up two regions with high density of enriched peaks and plot them.

```
> chrregions <- GRanges(c('chr2L', 'chr2R'), IRanges(start=c(100000, 200000), end=c(100100, 210000)))
> plotChrRegions(regions=chrregions, chrLength=c(chr2L=500000, chr2R=500000))
```




Figure 5: Chromosomal regions with a large number of hits. Red marks indicate regions with high concentration of peaks.

5 Plots

`stdPeakLocation` and `PeakLocation` produce a plot useful for exploring overall patterns in ChIP-chip or ChIP-seq experiments. Basically, it creates a density plot indicating where the peaks were located with respect to the closest gene/genomic feature. `stdPeakLocation` indicates the location in standardized coordinates, i.e. relative to each gene/features's length, which in some situations can help making genes/features comparable. `PeakLocation` produces the same plot in base pairs (i.e. non-standardized coordinates), which is useful as distances have a direct physical interpretation, e.g. to relate the peak location with nucleosome positioning. As mentioned earlier, function `annotatePeakInBatch` from package `ChIPpeakAnno` can be used to find the gene closest to each region. For illustrative purposes here we assign a fake gene to each region. The fake genes start, end, strand and distance from the start to the region by default are assumed to be stored in `'start_position'`, `'end_position'`, `'strand'` and `'distance'`, respectively (although different names can be given as arguments to `PeakLocation` and `stdPeakLocation`).

```
> set.seed(1)
> peaksanno <- peaks
> mcols(peaksanno)$start_position <- start(peaksanno) + runif(length(peaksanno), -500, 1000)
> mcols(peaksanno)$end_position <- mcols(peaksanno)$start_position + 500
> mcols(peaksanno)$distance <- mcols(peaksanno)$start_position - start(peaksanno)
```


NULL




Figure 6: Distribution of peaks around the closest gene

```
> strand(peaksanno) <- sample(c('+','-'),length(peaksanno),replace=TRUE)
> PeakLocation(peaksanno,peakDistance=1000)
```

NULL

Figure 6 shows the resulting plot. We see that most of the peaks occur right around the transcription start site.

Two related functions are `regionsCoverage` and `gridCoverage`, which evaluate the coverage on user-specified genomic regions. We illustrate their use by obtaining the coverage for the regions which we found to be enriched (as previously described). `regionsCoverage` computes the coverage in the specified regions. As each region has a different length it may be hard to compare coverages across regions, e.g. to cluster regions with similar coverage profiles. `gridCoverage` simplifies this task by evaluating the coverage on a regular grid of 500 equally spaced points between the region start and end. The result is stored in an object of class `gridCover`. The object contains the coverage, which can be accessed with the method `getViewInfo`.

```
> cover <- coverage(ip)
> rcov <- regionsCoverage(seqnames(regions),start(regions),end(regions),cover=cover)
> names(rcov)

[1] "views"      "viewsInfo"

> rcov[['views']]
```

```
RleViewsList of length 1
$chr2L
Views on a 499998-length Rle subject
```

```
views:
```

```
      start   end width
[1] 66674 67923 1250 [5 5 6 6 6 6 7 7 7 7 7 7 8 7 8 8 8 8 8 ...]
[2] 72428 73199   772 [ 8 8 9 9 9 9 7 7 8 8 8 7 ...]
[3] 73357 74080   724 [ 3 5 5 6 6 6 6 7 7 7 7 7 ...]
[4] 74484 74484     1 [10]
[5] 86284 86285     2 [10 10]
[6] 86294 87202   909 [ 9 11 11 10 10 11 11 12 13 13 13 13 ...]
[7] 94761 95804  1044 [ 8 8 9 10 10 10 10 9 9 9 9 ...]
[8] 102246 103756 1511 [4 4 4 4 4 4 4 6 6 4 4 4 4 4 4 4 ...]
[9] 105518 106937 1420 [ 6 6 6 6 6 8 9 9 7 7 7 7 ...]
...
[42] 419857 420830   974 [ 7 8 8 8 8 9 10 10 11 11 15 17 ...]
[43] 420838 421573   736 [12 15 18 21 25 29 36 36 38 39 42 45 ...]
[44] 431005 432315  1311 [5 6 6 6 6 6 6 7 7 7 7 7 8 7 7 7 5 ...]
[45] 432329 432406    78 [10 11 12 12 12 13 13 13 12 14 14 15 ...]
[46] 452450 454178  1729 [ 8 11 13 14 13 14 14 14 14 15 16 17 ...]
[47] 472986 474752  1767 [ 6 7 8 8 8 8 8 8 7 7 8 9 ...]
[48] 477772 478378   607 [6 6 6 7 7 7 7 8 7 7 7 7 7 7 7 ...]
[49] 478619 480611  1993 [ 7 7 7 7 8 8 8 8 8 8 8 7 ...]
[50] 490766 491695   930 [2 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 4 4 ...]
```

```
> gridcov <- gridCoverage(rcov)
> dim(getCover(gridcov))
```

```
[1] 50 500
```

```
> getViewsInfo(gridcov)
```

```
DataFrame with 50 rows and 3 columns
```

	strand	meanCov	maxCov
	<factor>	<numeric>	<integer>
chr2L	+	20.6408	51
chr2L	+	105.581606217617	244
chr2L	+	54.5718232044199	129
chr2L	+	10	10
chr2L	+	10	10
...
chr2L	+	216.27009832273	1033
chr2L	+	110.716468590832	575
chr2L	+	13.1581548599671	41
chr2L	+	112.990466633216	585
chr2L	+	53.2333333333333	187

We plot the coverage for the selected regions and see that they present different profiles Figure 7, which suggests the use of some clustering technique to find subgroups of regions behaving similarly.




Figure 7: Coverage for some selected regions

```
> ylim <- c(0,max(getViewsInfo(gridcov)[['maxCov']]))
> plot(gridcov, ylim=ylim,lwd=2)
> for (i in seq_along(regions)) lines(getCover(gridcov)[i,], col='gray', lty=2)
```

References

- B. Efron, R. Tibshirani, J.D. Storey, and V. Tusher. Empirical Bayes analysis of a microarray experiment. *Journal of the American Statistical Association*, 96:1151–1160, 2001.
- J.L. Gastwirth. The estimation of the Lorenz curve and Gini index. *The review of economics and statistics (The MIT press)*, 54:306–316, 1972.
- C. Gini. *Variabilita e mutabilita*. C. Cuppini, Bologna, 1912.
- A. Mortazavi, B.A. Williams, K. McCue, L. Schaeffer, and B. Wold. Mapping and quantifying mammalian transcriptomes by rna-seq. *Nature methods*, 5:621–628, 2008.
- E. Planet, C. Stephan-Otto Attolini, O. Reina, O. Flores, and D. Rossell. htseqtools: High-throughput sequencing quality control, processing and visualization in r. *Bioinformatics (in press)*, 2012.

Y. Zhang, T. Liu, C.A. Meyer, J. Eeckhoute, D.S. Johnson, B.E. Bernstein, C. Nussbaum, R.M. Myers, M. Brown, W. Li, and X.S. Liu. Model-based analysis of chip-seq (macs). *Genome Biology*, 9:R173, 2008.